UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/585,711	07/10/2006	Paolo Falcioni	108041-19	4344	
Patricia A. Shee	7590 06/22/201 ehan	EXAMINER			
Cesari and McKenna, LLP			TUN, NAY L		
88 Black Falcon Avenue Boston, MA 02210			ART UNIT	PAPER NUMBER	
ŕ				2612	
			MAIL DATE	DELIVERY MODE	
			06/22/2011	PAPER	

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)			
Office Astion Occurs	10/585,711	FALCIONI ET AL.			
Office Action Summary	Examiner	Art Unit			
	NAY TUN	2612			
The MAILING DATE of this communication app Period for Reply	pears on the cover sheet with the c	orrespondence address			
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DARWING STATE OF THE MAILING DARWING STATE OF THE MAILING DAWNING THE MONTHS From the mailing date of this communication. If NO period for reply is specified above, the maximum statutory period of Failure to reply within the set or extended period for reply will, by statute. Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tim will apply and will expire SIX (6) MONTHS from a cause the application to become ABANDONE	ely filed the mailing date of this communication. (35 U.S.C. § 133).			
Status					
Responsive to communication(s) filed on <u>27 A</u> This action is FINAL . 2b) ☑ This Since this application is in condition for allowar closed in accordance with the practice under E	action is non-final. nce except for formal matters, pro				
Disposition of Claims					
 4) ☐ Claim(s) 30,31,33-48,50 and 51 is/are pending in the application. 4a) Of the above claim(s) is/are withdrawn from consideration. 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 30,31,33-48,50 and 51 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/or election requirement. 					
Application Papers					
9) The specification is objected to by the Examine 10) The drawing(s) filed on is/are: a) accomplicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the Examine	epted or b) objected to by the Eddrawing(s) be held in abeyance. See ion is required if the drawing(s) is obj	e37 CFR 1.85(a). ected to. See 37 CFR 1.121(d).			
Priority under 35 U.S.C. § 119					
 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 					
Attachment(s) 1) \(\overline{\text{N}} \) Notice of References Cited (PTO-892)	4) 🔲 Interview Summary				
Notice of Draftsperson's Patent Drawing Review (PTO-948) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date	Paper No(s)/Mail Da 5) Notice of Informal P 6) Other:	ite			

Art Unit: 2612

DETAILED ACTION

Continued Examination Under 37 CFR 1.114

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on April 27, 2011 has been entered. Claims 1-29, 32 and 49 have been cancelled, claims 50-51 have been newly added and claims 30-31, 33, 37, 41 and 47 have been amended. Therefore, claims 30-31, 33-48 and 50-51 are currently pending for examination.

Claim Objections

2. Claims 40 and 47 are objected to because of the following informalities: Claim 40 recites "quantitybeing" in line 4 and Claim 47 recite "n electronic control means" in line 11 which appears to be typographical errors. Appropriate correction is required.

Claim Rejections - 35 USC § 112

3. The following is a quotation of the first paragraph of 35 U.S.C. 112:

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

4. Claims 47-48 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was not

described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention.

Claim 47 recites "the one ore more internal sensors measure ... one or more electrical quantities" in lines 12-13 which is considered as a new matter because according to the specification Fig. 1 elements 20A, 20B, 9 and Paragraph [0028] of the application publication, the electric quantity are external. Please provide the support in the specification (Page, line or paragraph numbers) if the Examiner is mistaken. Claim 48 is also rejected since it depends from rejected claim 47.

Claim Rejections - 35 USC § 112

5. The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

6. Claims 30-31, 33-48 and 50 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Claim 30 recites "the monitoring device" in line 19 and Claims 31, 33-36, 38-40 recite "the monitoring device" in line 1 without sufficient antecedent basis in the claims. For the purpose of examination, Examiner will assume "the monitoring device" as "the monitoring system".

Claim 30 recites "an external sensor" in lines 15-16. It is unclear that it is the same "one or more "external sensors" recited in lines 13-14. For the purpose of examination, Examiner will

assume "an external sensor" as "said one or more external sensor".

Claim 30 recites "the at least one physical quantity" in line 20-21 and "at least one physical quantity" in lines 22-23. It is unclear that it is referring to "a plurality of physical quantities" recited in line 4 or not. For the purpose of examination, Examiner will assume as "said plurality of physical quantities".

Claim 30 recites "at least one electric quantity" in line 23 and "one ore more electrical quantities" in lines 25-26. It is unclear that it is the same "at least one electric quantity" recited in line 18 or not. For the purpose of examination, Examiner will assume as "the at least one electric quantity".

Claims 31, 33-36, 38-40 and 50 are also rejected since they depend from rejected claim 30.

Claim 41 recites "external physical quantities" in line 13. It is unclear that it is the same "plurality of external physical quantities" recited in line 5 or not. For the purpose of examination, Examiner will assume as "said plurality of external physical quantities".

Claim 41 recites "an internal physical quantity" in line 15-16. It is unclear that it is the same "plurality of internal physical quantities" recited in line 5 or not. For the purpose of examination, Examiner will assume as "said plurality of internal physical quantities".

Claim 41 recites "the one or more internal sensors" in line 16-17 without proper antecedent basis in the claim. For the purpose of examination, Examiner will assume as "said plurality of internal physical sensors".

Claim 41 recites "one or more internal physical quantities, one or more external physical quantities, or both, and one or more electric quantities" in line 22-24. It is unclear that it is the

Art Unit: 2612

same "plurality of internal physical quantities", "plurality of external physical quantities" and "plurality of electric quantities" recited in lines 4-5 or not. For the purpose of examination, Examiner will assume as "one or more of said internal physical quantities, one or more of said external physical quantities, or both, and one or more of said electric quantities".

Claim 41 recites "said at least one physical quantity" without proper antecedent basis in the claim. For the purpose of examination, Examiner will assume as "at least one of said internal and external physical quantities".

Claims 37 and 42-46 are also rejected since they depend from the rejected claim 41.

Claim 43 recites "the communication means" and claim 45 recites "the first communication means" without proper antecedent basis in the claim. For the purpose of examination, Examine will assume as "the one or more external sensors".

Claim 47 recites "a plurality of" external physical quantities or internal physical quantities or electrical quantities in some places and "one or more" external physical quantities or internal physical quantities or electrical quantities in some other places. It is unclear they are referring to the same internal, external physical quantities and electric quantities.

Claim 47 recites "the first interface means" in line 10 without proper antecedent basis in the claim. Claim 48 is also rejected since it depends from rejected claim 47.

Claim Rejections - 35 USC § 102

7. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

Art Unit: 2612

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

8. Claim 51 is rejected under 35 U.S.C. 102(b) as being anticipated by **Appel** et al. (**Appel**: US 2003/0116177).

Regarding Claim 51, Appel discloses a system for monitoring a washing machine, comprising

a flow sensor positioned along an associated inlet pipe externally to said washing machine and adapted to measure water flow rate supplied to the washing machine; a conductivity sensor positioned along a drain pipe adapted to measure the conductivity of washing liquid as the liquid drains from the washing machine (Paragraph [0014]: sensor for water inlet flow and sensor fro degree of soiling through conductivity measurement and sensors can be installed in the drain or in the conduit leading into the dispensing compartment and Paragraph [0013] & [0026]: sensors are non-intrusively connected with the existing washing machine without invading of the machine housing);

a microcontroller configured to receive measurements from sensors associated with the washing machine; a dedicated communication network having a coupling to the flow sensor and the conductivity sensor, said network being coupled externally of the washing machine to the microcontroller (Paragraph [0014]: sensors can be wiredly or wirelessly remotely connected with the means of receiving signals in the container house and the computer program controls the dispensing sequence based on the combinations of sensor readings. A microcontroller is necessitated to execute the computer program. Paragraph [0013] & [0026]: sensors are non-intrusively connected with the existing washing machine without invading of the machine

Art Unit: 2612

housing); and

a read and write memory storing a plurality of measurements of at least one physical quantity relating to the washing machine's operation, to provide a historical analysis of the operation of the washing machine (Paragraph [0014]: a database in which the results of various readings are stored).

Claim Rejections - 35 USC § 103

- 9. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
- (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

The factual inquiries set forth in <u>Graham v. John Deere Co., 383 U.S. 1, 148 USPQ 459</u> (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows: (See MPEP Ch. 2141)

- a. Determining the scope and contents of the prior art;
- b. Ascertaining the differences between the prior art and the claims in issue;
- c. Resolving the level of ordinary skill in the pertinent art; and
- d. Evaluating evidence of secondary considerations for indicating obviousness or nonobviousness.
- 10. Claims 30-31, 33-48 and 50 are rejected under 35 U.S.C. 103(a) as being unpatentable over **Natalini** et al (**Natalini**: US 2002/0095269) in view of **Appel**, further in view of **Sharood** et al. (**Sharood**: US 6,453,687) further in view of **Shibaki** et al. (**Shibaki**: US 5,960,234).

Regarding Claim 30, Natalini discloses a system for monitoring a household electric appliance being a washing machine, the monitoring system comprising:

i. a read and write memory storing a plurality of measurements of a plurality of physical

quantities quantity relating to the household electric appliance within a predetermined time period during a treatment cycle (Paragraph [0027]: the readings of various sensors are continuously monitored and memory 35 retains monitored information/sensor data for at least the last operating cycle i.e. within the time period of a treatment cycle and Paragraph [0040]: monitored information/sensor data include physical quantities related to the washing machine),

ii. a first interface means to connect to one or more sensors for measuring said plurality of physical quantities of the household electric appliance, including one or more internal sensors for measuring internal physical quantities (Paragraph [0040-0041 & 0027]: monitoring subsystem 32 receives the functional data from sensors via bus 222);

iv. a means for measuring at least one electric quantity by measuring an electric current (Paragraph [0040]: current sensor 124 measures current drawn);

v. a storage means containing one or more predefined values of the at least one physical quantity (Paragraph [0041]: sensor data are compared with the expected values and/or values from past cycles. A storage means is necessitated);

vi. a microcontroller to process a particular combination of at least one physical quantity and the at least one electric quantity to determine an actual combination of the internal physical quantities, one or more external physical quantities or both and one or more electrical quantities at an instant in time (Paragraph [0041]: the monitoring subsystem analyzes/processes the functional data from the sensors associated with the most recent operating cycle and Paragraph [0040]: monitored information/sensor data are combination of physical and electrical quantities),

to compare said actual combination to one or more respective predefined values contained in the storage means to determine at least one piece of information, each predefined

value being a threshold value against which an actual value is compared to determine a proper operation of a particular component of the appliance at that instant in time (Paragraph [0040-0041]: the monitoring subsystem compares the sensor data with the expected values and/or values from past cycles to determine whether the washing machine is operating properly.

Paragraph [0040]: monitored information/sensor data are combination of physical and electrical quantities); and

vii. a second interface means to send the at least one piece of information to a remote center for storage (Fig. 1 and 2, network interface 37 to gateway 42 and Paragraph [0054]: gateway retains data).

Natalini does not explicitly disclose the read write memory storing a plurality of external physical quantities or a first interface means to connect a dedicated external communications network to a plurality of external physical sensors, which measure external physical quantities.

However, **Appel** teaches installing sensors non-intrusively to an existing washing machine, without requiring to invade the machine housing i.e. external sensors (Paragraph [0013] and [0026]) and the external sensors includes water inlet flow and conductivity and can be placed in the drain or in the conduit leading into the dispensing compartment and the external sensors can be wired or wirelessly connected and the readings/measurements from such sensors can be stored in the database and used together with the electrical quantity to determine the function of a washing machine (Paragraph [0014]).

Therefore, it would have been obvious to the one of the ordinary skill in the art at the time of the invention was made to provide the external sensors and measurements of external physical quantities, as taught by **Appel**, as a known technique of sensor installation in the base

device of the appliance with predictable result of retrofitting and as known measurements in the base process of appliance monitoring with the predictable result of determining the function/cycle of a washing machine.

The combined system of **Natalini** and **Appel** does not explicitly disclose the current measured by the current sensor is running through the monitoring device or the storing of a last measured value of a physical quantity causing the deletion of a first measured value within said plurality of measurements in the read and write memory.

However, the preceding limitation is known in the art of monitoring appliances. **Sharood** discloses a current sensor that measures the current running through the monitoring device (**Sharood**: Col. 9 Lines 6-12 and Fig. 6b). Therefore, it would have been obvious to the one of the ordinary skill in the art at the time of the invention was made to measure the current running through the monitoring device as a known technique of sensing the current draw in the base device of the appliance with the predictable result of monitoring the functions of the appliance related to the current.

The combined system of **Natalini**, **Appel** and **Sharood** does not explicitly disclose the storing of a last measured value of a physical quantity causing the deletion of a first measured value within said plurality of measurements in the read and write memory.

However, the preceding limitations are known in the art of memory management.

Shibaki discloses the storing of newly generated data causing the deletion of the oldest data (col. 6 lines 58-60). Therefore, it would have been obvious to the one of the ordinary skill in the art at the time of the invention was made to manage memory as taught by Shibaki in the combined system of Natalini and Sharood, as the known technique of storage in the base device of

memory with the predictable results of saving the newest information when there is no empty space left in the memory.

Regarding Claim 50, the combined system of Natalini, Appel, Sharood and Shibaki discloses the system as defined in claim 30 and further discloses wherein the external sensors include further comprising: a flow sensor positioned along an associated inlet pipe and adapted to measure water flow rate supplied to the washing machine; and a conductivity sensor positioned along a drain pipe adapted to measure the conductivity of washing liquid drained from the washing machine (Paragraph [0014]).

Regarding claim 31, the combined system of Natalini, Appel, Sharood, and Shibaki discloses the device of claim 30 as discussed above and further discloses at least one internal sensor within the household electric appliance where the at least one internal sensor measures a physical quantity of an internal part of the household device and that the microcontroller further processes the measurements (Natalini: Paragraph [0040-0041]: a second physical quantity is sensed and processed) and a wireless communication device within the first interface means, said wireless communication device also adapted to function as the dedicated communication network that couples the external sensors that sense the external physical quantities to said first interface means (Appel: Paragraph [0014]: wireless connection to external sensors), and further to report electrical measurements (Natalini: Paragraph [0026]).

The combined system does not explicitly disclose the communication between wireless communication device and at least one internal sensor.

However, **Sharood**, in another embodiment of the disclosed invention, teaches that the first interface means (and associated sensor) and monitoring device can be separate units and that

Art Unit: 2612

the first interface means (and associated sensor) can be connected to the monitoring device (and therefore communication means) by another interface (element 2704, figure 27B and column 28 lines 65-67). It would have been obvious to one of ordinary skill in the art at the time on the invention to use a wireless connection as the interface to reduce the amount of cabling used thereby making it easier to connect the sensor to the monitoring device and increasing the ease of installation and modification (i.e. not limited to a certain cable length).

Regarding claim 33, the combined system of Natalini, Appel, Sharood and Shibaki discloses the device of claim 30 as discussed above. The combination further discloses a timing unit, where the timing unit determines time to be associated with the measurements of the one or more physical quantities and at least one electrical quantity (Natalini: Paragraph [0027]: the subsystem combines the functional data i.e. physical and electrical quantities into historical data, Paragraph [0050]: historical data are associated with the time).

Regarding claim 34, the combined system of Natalini, Appel, Sharood and Shibaki discloses the device of claim 30 as discussed above and further discloses that the at least one electrical quantity includes at least one of the following: momentary electric current drawn by the household electric appliance, line voltage applied to the household electric appliance, momentary electric power drawn by the household electric appliance, electric energy consumption of the household electric appliance within a predefined time period, a power factor of the load represented by the household electric appliance, $\cos(\varphi)$ of the load represented by the household electric appliance, and type of reactive power of the load represented by the household electric appliance (Natalini: Paragraph [0040-0041]: current drawn).

Regarding claim 35, the combined system of Natalini, Appel, Sharood and Shibaki

discloses the system of claim 30 as discussed above and further discloses that the first interface is connected to the one or more sensors through a wireless connection (**Appel**: Paragraph [0014]: external sensors can be connected wirelessly).

Regarding claim 36, the combined system of Natalini, Appel, Sharood and Shibaki discloses the system of claim 30 as discussed above. The combination further discloses that the second interface means is connected to the remote center through a wireless connection (Natalini: Paragraph [0026]).

Regarding claim 38, the combined system of Natalini, Appel, Sharood and Shibaki discloses the system of claim 30 as discussed above. The combination further discloses that said at least one physical quantity includes at least one of: temperature, flow rate, conductivity, weight, absolute humidity, relative humidity, pressure, linear displacement, linear velocity, linear acceleration, angular displacement, angular velocity, angular acceleration, chemical concentration, sound pressure, sound intensity, light intensity, oscillation frequency, and oscillation amplitude (Natalini: Paragraph [0040]: concentration of laundry detergent).

Regarding claim 39, the combined system of Natalini, Appel, Sharood and Shibaki discloses the system of claim 30 as discussed above and further discloses that an information storage means for storing the at least one piece of information in the read and write memory (Natalini: Fig. 3, step 312 and Paragraph [0037 and 0042]: the appropriate flag 228 is set to indicate that the alarm message that identifies the fault).

Regarding claim 40, the combined system of Natalini, Appel, Sharood and Shibaki discloses the system of claim 30 as discussed above and further discloses that the household electric appliance is one of a laundry washing machine and a washing/drying machine adapted to

perform at least one wash treatment on textile items, said at least one physical quantity being preferably at least one of the following: weight of the textile items being present in the basket of the washing machine or the washing/drying machine, flow rate of water supplied to the washing machine or the washing/drying machine, temperature of washing liquid contained in a tub of the washing machine or the washing/drying machine, and conductivity of the washing liquid drained by the washing machine or the washing/drying machine, where the washing liquid comprises water and at least one washing agent (**Natalini**: Paragraph [0040] washing machine 18 with sensor for concentration of the detergent. One of the ordinary skill in the art understands that concentration of the detergent can be sensed by the conductivity sensor).

Regarding Claim 41, Natalini discloses a monitoring device for use with a household electric appliance, the monitoring device comprising:

i. a read and write memory storing a plurality of measurements of a plurality of internal physical quantities, and a plurality of electrical quantities related to the household electric appliance, said measurement being taken within a predetermined time period during a treatment cycle (Paragraph [0027]: the readings of various sensors are continuously monitored and memory 35 retains monitored information for at least the last operating cycle i.e. within the time period of a treatment cycle and Paragraph [0040]: monitored information includes internal physical quantities and electrical quantities related to the washing machine),

ii. means for coupling a plurality of internal physical sensors for measuring an internal physical quantity of the household electric appliance (Paragraph [0041]: processor 33 and bus 222, Paragraph [0041]: monitoring subsystem 32 receives the functional data from sensors and Paragraph [0040]: sensors are internal), where the one or more internal sensors are connected to

the monitoring device by way of an electronic control means and the first interface means (Fig. 2 and Paragraph [0041], processor 33 and Bus 222);

iii. a means for measuring at least one electric quantity by measuring an electric current (Paragraph [0040]: current sensor 124 measures current drawn);

iv. a microcontroller configured to:

a) process measurements of a combination of one or more internal physical quantities, one or more external physical quantities, or both, and one or more electric quantities to determine at least one piece of information relating to or being employed in said treatment cycle during operation of the household electric appliance, where the at least one piece of information includes at least one of: functional information, statistical information, and diagnostic information relating to the household electric appliance (Paragraph [0041]: the monitoring subsystem determines whether the washing machine is operating properly i.e. the functional information by analyzing/processing the functional data from the sensors and Paragraph [0040] the functional data from sensors includes physical and electrical quantities) by comparing a value of said one physical quantity with one or more predefined values that relate to values for the treatment being performed by the appliance at an instant in time (Paragraph [0040-0041]: the monitoring subsystem compares the sensor data with the expected values and/or values from past cycles); and

v. an information storage means for storing the at least one piece of information in the read and write memory (Fig. 3, step 312 and Paragraph [0037 and 0042]: the appropriate flag 228 is set to indicate that the alarm message that identifies the fault).

Natalini does not explicitly disclose the read write memory storing a plurality of external physical quantities or a first interface means to connect a dedicated external communications network to a plurality of external physical sensors, which measure external physical quantities.

Page 16

However, **Appel** teaches installing sensors non-intrusively to an existing washing machine, without requiring to invade the machine housing i.e. external sensors (Paragraph [0013] and [0026]) and the external sensors includes water inlet flow and conductivity and can be placed in the drain or in the conduit leading into the dispensing compartment and the external sensors can be wired or wirelessly connected and the readings/measurements from such sensors can be stored in the database and used together with the electrical quantity to determine the function of a washing machine (Paragraph [0014]).

Therefore, it would have been obvious to the one of the ordinary skill in the art at the time of the invention was made to provide the external sensors and measurements of external physical quantities, as taught by **Appel**, as a known technique of sensor installation in the base device of the appliance with predictable result of retrofitting and as known measurements in the base process of appliance monitoring with the predictable result of determining the function/cycle of a washing machine.

The combined device of **Natalini** and **Appel** does not explicitly disclose the measured current is the current running through the monitoring device or extrapolation from said plurality of measurements of said at least one physical quantity a data packet representative of the evolution of said at least one physical quantity within said predefined time period over one or more treatment cycles.

However, the preceding limitation is known in the art of monitoring appliances. Sharood

discloses a current sensor that measures the current running through the monitoring device (Sharood: Col. 9 Lines 6-12 and Fig. 6b). Therefore, it would have been obvious to the one of the ordinary skill in the art at the time of the invention was made to measure the current running through the monitoring device as a known technique of sensing the current draw in the base device of the appliance with the predictable result of monitoring the functions of the appliance related to the current.

Sharood further discloses an appliance monitoring system that extrapolates the time of failure from the measured conditions at intervals designated by the user (**Sharood**: Col. 27, lines 30-40: calculating the speed at which temperature is rising to estimate i.e. extrapolate how long it will be until food spoilage occurs). **Natalini** also teaches that warning for an appliance is also desirable before the actual failure occurs (Paragraph [0044]).

Therefore, it would have been obvious to the one of the ordinary skill in the art at the time of the invention was made to extrapolate a data packet from the measurements of said at least one physical quantity over a predetermined time period, as taught by **Sharood**, in the system of **Natalini** and **Appel**, as a known improvement in the base device of appliance monitoring system, with the predictable result of preventing the imminent failure.

The combined system of **Natalini**, **Appel** and **Sharood** does not explicitly disclose the storing of a last measured value of said at least one physical quantity causing the deletion of a first measured value within said plurality of values in the read and write memory.

However, the preceding limitations are known in the art of memory management.

Shibaki discloses the storing of newly generated data causing the deletion of the oldest data (col. 6 lines 58-60). Therefore, it would have been obvious to the one of the ordinary skill in the art at

the time of the invention was made to manage memory as taught by **Shibaki** in the combined system of **Natalini**, **Appel** and **Sharood**, as the known technique of storage in the base device of memory with the predictable results of saving the newest information when there is no empty space left in the memory.

Regarding claim 37, the combined device of Natalini, Appel, Sharood and Shibaki discloses the device of claim 41 as discussed above. The combination further discloses that the household electric appliance includes one of: a clothes dryer, a washing/drying machine, a dishwasher, a refrigerator, a freezer, a refrigerator/freezer, an electric oven, a gas oven, a microwave oven, a gas cooking top, an electric cooking top, a magnetic induction cooking top, a kitchen hood, a conditioner, a gas boiler, an electric water heater, an air conditioner, a hair dryer, an iron, a Hi-Fi system, a mixer or any other electric kitchenware, a lighting device, an alarm device (Natalini: washing machine 18).

Regarding claim 42, the combined device of Natalini, Appel, Sharood and Shibaki discloses the device of claim 41 as discussed above. The combination further discloses that the first interface means is an electric cable to the one or more external sensors (Appel: Paragraph [0014], external sensors can be connected wiredly or wirelessly).

Regarding claim 43, the combined device of Natalini, Appel, Sharood and Shibaki discloses the device of claim 41 as discussed above. The combination further discloses that the first interface means is wirelessly connected to the communication means (Appel: Paragraph [0014], external sensors can be connected wiredly or wirelessly).

Regarding claim 44, the combined device of Natalini, Appel, Sharood and Shibaki discloses the device of claim 41 as discussed above. The combination further discloses that the

first interface means is wirelessly connected to the one or more external sensors (*Appel:* Paragraph [0014], external sensors can be connected wiredly or wirelessly).

Regarding claim 45, the combined device of Natalini, Appel, Sharood and Shibaki discloses the device of claim 41 as discussed above and further discloses that the first interface means is connected to the communication means (Appel: Paragraph [0014], external sensors can be connected wiredly or wirelessly).

Regarding claim 46, the combined device of Natalini, Appel, Sharood and Shibaki discloses the device of claim 41 as discussed above and further discloses that the communication means and the one or more internal sensors are connected through an electronic control means, where the electronic control means collect, stores, and processes the measurements from the one or more physical quantities from the one or more internal sensors (Natalini: Paragraph [0041] and Fig. 2, 37, subsystem 32 with processor 33 receives sensor data and send via network interface).

Regarding Claim 47, Natalini discloses a system for monitoring a household electric appliance, the system comprising:

a) a household electric appliance (Fig. 1, washing machine 18);

an electronic control means connected to one or more internal sensors, where the one or more internal sensors measure one or more physical internal quantities or one or more electrical quantities of the household electric appliance, the electronic control means configured to collect, store, and process measurements of the one or more physical and electrical internal quantities being internal measurements (*Paragraph [0041]: monitoring subsystem 32 receives and analyzes/processes the sensor data from sensors and stores the sensor data from past cycles*

Paragraph [0040]: sensors are internal and sensor data are measurements of physical quantities and electrical quantities);

a communication means communicating with the electronic control means to transfer one or more of said internal measurements, over a predetermined time period to a first interface means on a monitoring device (Paragraph [0041]: monitoring subsystem receives sensor data over the bus 222);

- e) the monitoring device including:
- a. a read and write memory storing a plurality of measurements of said plurality of internal physical quantities and a plurality of electrical quantities, within a predetermined time period, (Paragraph [0027]: the readings of various sensors are continuously monitored and memory 35 retains monitored information for at least the last operating cycle i.e. within the time period of a treatment cycle and Paragraph [0040]: monitored information includes physical quantities related to the washing machine),
- b. the first interface means to connect to the communication means to receive the measurements of the one or more physical internal quantities (Paragraph [0041]: monitoring subsystem receives sensor data over the bus 222),
- c. a means for measuring at least one electric quantity by measuring an electric current (Paragraph [0040]: current sensor 124 measures current drawn),
- d. a timing unit to associate an instant in time at which the measurements of the one or more physical quantities and the at least one electric quantity are taken (*Paragraph [0027]: the subsystem combines the functional data i.e. physical and electrical quantities into historical data, Paragraph [0050]: historical data are associated with the time)*,

Art Unit: 2612

e. a microcontroller configured to:

- (i) process the measurements of one or more physical internal quantities, and the at least one electric quantity, at the instant in time, to determine sensed information relating to the household electric appliance, where the sensed information includes functional information, statistical information, and diagnostic information relating to the household electric appliance (Paragraph [0040] the functional data from sensors includes physical and electrical quantities. Paragraph [0041]: the monitoring subsystem analyzes i.e. processes the functional data from the sensors and determines whether the washing machine is operating properly i.e. the functional information. Paragraph [0027]: statistical data. Paragraph [0042]: message that identifies the indicated fault), said sensed information being a combination of values of physical internal quantity and at least one electric quantity with a reference combination of physical and electrical quantities being the combination that best represents the proper operation of the appliance at that instant in time (Paragraph [0040-0041]: the monitoring subsystem compares the sensor data with the expected values and/or values from past cycles. The expected values and/or values from past cycles represents the proper operation of the appliance since the proper operation is determined based on comparison with these values), and
- (ii) collect information that allows the system to trace a history of the monitored electric appliance that permits the microprocessor to build in the read and write memory, profiles being indicative of a trend within a predefined time period of a particular physical quantity or typology of information obtained by the microcontroller based upon values detected by the sensors (*Paragraph [0027]: the subsystem also combines the*

functional data for a series of operating cycles into historical data and aggregates the historical data into statistical data that relates to all of the cycles performed by the intelligent appliance); and

f. a second interface means to send the at least one piece of information to a remote center (*Paragraph [0045] and Fig. 2, network interface 37*); and

g. the remote center configured to collect the at least one piece of information from one or more monitoring devices connected to respective household electric appliances and to extract statistical information about the household electric appliances being monitored (*Paragraph* [0031]).

Natalini does not explicitly disclose the read and write memory storing a plurality of external physical quantities or a first interface means to connect a dedicated external communications network to a plurality of external physical sensors, which measure external physical quantities.

However, **Appel** teaches installing sensors non-intrusively to an existing washing machine, without requiring to invade the machine housing i.e. external sensors (Paragraph [0013] and [0026]) and the external sensors includes water inlet flow and conductivity and can be placed in the drain or in the conduit leading into the dispensing compartment and the external sensors can be wired or wirelessly connected and the readings/measurements from such sensors can be stored in the database and used together with the electrical quantity to determine the function of a washing machine (Paragraph [0014]).

Therefore, it would have been obvious to the one of the ordinary skill in the art at the time of the invention was made to provide the external sensors and measurements of external

physical quantities, as taught by **Appel**, as a known technique of sensor installation in the base device of the appliance with predictable result of retrofitting and as known measurements in the base process of appliance monitoring with the predictable result of determining the function/cycle of a washing machine.

The combined system of **Natalini** and **Appel** does not explicitly disclose the measured current is the current running through the monitoring device or extrapolation from said plurality of measurements of said at least one physical quantity a data packet representative of the evolution of said at least one physical quantity within said predefined time period over one or more treatment cycles.

However, the preceding limitation is known in the art of monitoring appliances. **Sharood** discloses a current sensor that measures the current running through the monitoring device (**Sharood**: Col. 9 Lines 6-12 and Fig. 6b). Therefore, it would have been obvious to the one of the ordinary skill in the art at the time of the invention was made to measure the current running through the monitoring device as a known technique of sensing the current draw in the base device of the appliance with the predictable result of monitoring the functions of the appliance related to the current.

Sharood further discloses an appliance monitoring system that extrapolates the time of failure from the measured conditions at intervals designated by the user (**Sharood**: Col. 27, lines 30-40: calculating the speed at which temperature is rising to estimate i.e. extrapolate how long it will be until food spoilage occurs). **Natalini** also teaches that warning for an appliance is also desirable before the actual failure occurs (Paragraph [0044]).

Therefore, it would have been obvious to the one of the ordinary skill in the art at the

time of the invention was made to extrapolate a data packet from the measurements of said at least one physical quantity over a predetermined time period, as taught by **Sharood**, in the system of **Natalini and Appel**, as a known improvement in the base device of appliance monitoring system, with the predictable result of preventing the imminent failure.

The combined system of **Natalini**, **Appel** and **Sharood** does not explicitly disclose the storing of a last measured value of said at least one physical quantity causing the deletion of a first measured value within said plurality of values in the read and write memory.

However, the preceding limitations are known in the art of memory management.

Shibaki discloses the storing of newly generated data causing the deletion of the oldest data (col. 6 lines 58-60). Therefore, it would have been obvious to the one of the ordinary skill in the art at the time of the invention was made to manage memory as taught by Shibaki in the combined system of Natalini, Appel and Sharood, as the known technique of storage in the base device of memory with the predictable results of saving the newest information when there is no empty space left in the memory.

Regarding claim 48, the combined system of Natalini, Appel, Sharood and Shibaki discloses the system of claim 47 as discussed above. Natalini further discloses that the remote center receives a plurality of information sent by the monitoring device that the remote center collects and sorts for the purpose of identifying at least one parameter related to the operation of a washing machine or a washing/drying machine, the at least one parameter being preferably at least one of the following: number of wash treatments performed by the washing machine or the washing/drying machine within a predefined time interval, quantity and typology of textile items loaded on average by a user for each wash treatment, quantity and typology of washing agents

Art Unit: 2612

loaded on average by the user for each wash treatment, average quantity of water used by the washing machine or the washing/drying machine for each wash treatment, and average electric energy absorbed by the washing machine or the washing/drying machine for each wash treatment (Paragraph [0069]).

Response to Arguments

11. Applicant's arguments filed on April 27, 2011 have been fully considered but they are moot in view of new grounds of rejections.

Contact Information

12. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Nay Tun whose telephone number is (571) 270-7939. The examiner can normally be reached on Mon-Thurs from 9:00-5:00.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's Supervisor, Daniel Wu can be reached on (571) 272-2964. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306. Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

/NAY TUN/

/DANIEL WU/ Supervisory Patent Examiner, Art Unit 2612